

GreenFilm 100 PP LUVES M W air rem. grey adh FR

Technical Datasheet

L Latex · UV UV curing · ES Eco Solvent · S Solvent · M Matt · W White · air structured liner · rem. removable · grey adhesive · adh self-adhesive · FR Flame Retardant

Version: 03-2022

Inks



Application and Properties



Technical Data

PP Film thickness:	100 µm
Total thickness:	approx. 240 µm (incl. adhesive and liner)
Composition:	PP (BOPP) + grey reversible acrylic adhesive + embossed paper, single sided siliconized, double-sided PE coated
Liner:	135 g/m ² embossed, double-sided PE-coated paper
Surface:	matte white
Adhesive:	Grey, Water-based, Removable acrylic adhesive
Adhesive Power:	Initial adhesive power: 3,7 N/25 mm, after 20 min: 3,3 N/25 mm; after 24h: 8,0 N/25 mm

General Information

- 100 µm white matte biaxial oriented (BOPP) polypropylene film
- 100% PVC free
- Recyclable
- No VOC emissions (volatile organic compounds)
- Bubble-free adhesion
- Reversible/removable, grey adhesive
- Suitable for indoor and outdoor application
- Printable with latex, UV-curable, eco solvent and solvent inks
- Fast drying
- High colour brilliance
- Good water and scratch resistance

Application

- Labels, stickers, signs, markings
- Quick and easy interior decoration
- Wall covering
- Events, trade fair and shop fitting
- Short - medium term outdoor application / Signage

Advantages

- Environmentally friendly
- Recyclable
- 100% PVC free
- Easy, bubble-free application
- Reversible adhesive with good, reliable adhesion

GreenFilm 100 PP LUVESS M W air rem. grey adh FR

Technical Datasheet

L Latex · UV UV curing · ES Eco Solvent · S Solvent · M Matt · W White · air structured liner · rem. removable · grey
adhesive ·
adh self-adhesive · FR Flame Retardant

Version: 03-2022

- Grey adhesive allows for direct application on previously printed surfaces

Printing Properties

- Excellent printability with latex, UV curing, eco solvent and solvent inks
- No bleedings even with high ink limit
- Fast drying
- High colour brilliance

Processing instructions

- The print must be completely dry before further processing; a drying time of 24 hours is recommended
- The surface must be dry, clean, absorbent and smooth
- Roller or felt squeegee recommended to be without sharp edges
- To avoid fingerprints, the use of cotton gloves is recommended
- The optimal working condition during processing is 18° - 25°C and a relative humidity of 40% - 65%
- When removing/disassembling, make sure that the GreenFilm is not torn off suddenly, but is pulled off slowly.

More information

- You can find more information on our products on www.com2-c.de
- The print side of the materials as well as the lengths and widths can be customized to your needs prior to a MOQ
- Always store rolls together with the label or batch number. No complaints can be processed without a batch number.
- Our tests are carried in standard climate conditions
- Shelf life in the original packaging, 2 years when storing properly at 15° - 20°C
- Durability: indoor up to 2 years (unprinted), outdoor up to 1 years (unprinted)

Available sizes

- 50 m x 137,0 cm (54'')

This technical information was made and assessed based on the latest technology and our experience. Due to various parameters and conditions under which the described product is used, we re-command that every user should check the product for its suitability for the intended uses. A legally binding assurance of certain properties cannot be derived from our information. Errors and changes are subjected. With the release of a new version, this datasheet version will not be valid.