


Backlit 210 PET LUVESS SM W Plus

Technical Datasheet


L Latex · UV UV curing · ES Eco Solvent · S Solvent · SM Satin · W White

Version: 03-2022

Inks



Application and Properties



Technical Data

Thickness:	approx. 210µm
Composition:	100% polyester
Surface:	Satin white
Reverse side:	Glossy

General Information

- 100% polyester film
- Printable with latex, UV curing, eco solvent and solvent inks
- High-quality satin inkjet coating enables extremely high ink limit
- Fast drying
- Extremely high color brilliance
- Good water and scratch resistance
- Dimension stability

Application

- Indoor advertising
- Specially developed for City lights and Light boxes
- For universal front print application

Advantages

- Splash-proof, high-quality inkjet coating
- Fast drying, no bleeding even with high ink limits
- Strong and brilliant colors with extremely high ink application
- Dimension stability Polyester composite
- Material can be used without lamination

Printing Properties

- Excellent printability with latex, UV curing, eco solvent and solvent inks
- High ink limit application possible due to high-quality inkjet coating
- Very good and fast drying
- High color brilliance
- Waterproof inkjet coating

Backlit 210 PET LUVESSE SM W Plus

Technical Datasheet

L Latex · UV UV curing · ES Eco Solvent · S Solvent · SM Satin · W White

Version: 03-2022

Processing instructions

- The print must be completely dry before further processing; a drying time of 24 hours is recommended
- The optimal working condition during processing is 18° - 25°C and a relative humidity of 40% - 65%

More information

- You can find more information on our products on www.com2-c.de
- The print side of the materials as well as the lengths and widths can be customized to your needs prior to a MOQ
- Always store rolls together with the label or batch number. No complaints can be processed without a batch number.
- Our tests are carried in standard climate conditions
- Shelf life in the original packaging, 1 year when storing properly at 18° - 20°C

Available sizes

- 30 m x 110 cm (42") | 30 m x 137 cm (54") | 30 m x 152 cm (60")
50 m x 110 cm (42") | 50 m x 137 cm (54") | 50 m x 152 cm (60")

This technical information was made and assessed based on the latest technology and our experience. Due to various parameters and conditions under which the described product is used, we re-recommend that every user should check the product for its suitability for the intended uses. A legally binding assurance of certain properties cannot be derived from our information. Errors and changes are subjected. With the release of a new version, this datasheet version will not be valid.

Backlit 210 PET LUVESS SM W Plus

Technical Datasheet

L Latex · UV UV curing · ES Eco Solvent · S Solvent · SM Satin · W White

Version: 03-2022